

Technical Data

Model	SUN-10K-G06 P3-EU-AM2
PV String Input Data	
Max. PV Input Power (kW)	15
Max. PV Input Voltage (V)	1100
Start-up Voltage (V)	140
MPPT Voltage Range (V)	120-1000
Rated PV Input Voltage (V)	600
Max. Operating PV Input Current (A)	13+13
Max. Input Short Circuit Current (A)	19.5+19.5
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1
AC Output Side	
Rated AC Output Active Power (kW)	10
Max. AC Output Apparent Power (kVA)	11
Rated AC Output Current (A)	15.2/14.5
Max. AC Output Current (A)	16.7/16
Rated Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un
Grid Connection Form	3L/N/PE
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65
Power Factor Adjustment Range	0.8 leading to 0.8 lagging
Total Current Harmonic Distortion THDi	<3%
DC Injection Current	<0.5In
Efficiency	
Max. Efficiency	98.3%
Euro Efficiency	97.8%
MPPT Efficiency	>99%
Equipment Protection	
DC Polarity Reverse Connection Protection	Yes
AC Output Overcurrent Protection	Yes
AC Output Overvoltage Protection	Yes
AC Output Short Circuit Protection	Yes
Thermal Protection	Yes
DC Terminal Insulation Impedance Monitoring	Yes
DC Component Monitoring	Yes
Ground Fault Current Monitoring	Yes
Arc Fault Circuit Interrupter (AFCI)	Optional
Power Network Monitoring	Yes
Island Protection Monitoring	Yes
Earth Fault Detection	Yes
Overvoltage Load Drop Protection	Yes
Residual Current (RCD) Detection	Yes
Surge Protection Level	TYPE II(DC), TYPE II(AC)
Interface	
Communication Interface	RS485/RS232
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)
General Data	
Operating Temperature Range (°C)	-25 to +60°C, >45°C Derating
Permissible Ambient Humidity	0-100%
Permissible Altitude (m)	4000m
Noise (dB)	<45
Ingress Protection(IP) Rating	IP 65
Inverter Topology	Non-Isolated
Over Voltage Category	OVC II(DC), OVC III(AC)
Cabinet Size (WxHxD mm)	283×463×178 (Excluding Connectors and Brackets)
Weight (kg)	11
Type of Cooling	Natural Cooling
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G98, G99, VDE-AR-N 4105
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2